



# T32S Series Sideshifting General Purpose Hydraulic Clamp



| Model No.     | Capacity @ 24" LC | Range Inside Arms | Arm Length | Arm Height | Mtg | Weight | ET  | HCG | VCG  | A  | B    | C    |
|---------------|-------------------|-------------------|------------|------------|-----|--------|-----|-----|------|----|------|------|
| T32-25-30-18S | 2500              | 22 - 64           | 30         | 18         | II  | 857    | 4.4 | 7.2 | 10.4 | 36 | 21.0 | 2.13 |
| T32-25-36-18S | 2500              | 22 - 64           | 36         | 18         | II  | 870    | 4.4 | 7.7 | 10.4 | 36 | 21.0 | 2.13 |
| T32-25-30-24S | 2500              | 22 - 64           | 30         | 24         | II  | 878    | 4.4 | 7.5 | 10.6 | 36 | 21.0 | 2.13 |
| T32-25-36-24S | 2500              | 22 - 64           | 36         | 24         | II  | 896    | 4.4 | 8.1 | 10.7 | 36 | 21.0 | 2.13 |
| T32-25-30-30S | 2500              | 22 - 64           | 30         | 30         | II  | 900    | 4.4 | 7.8 | 11.0 | 36 | 21.0 | 2.13 |
| T32-25-36-30S | 2500              | 22 - 64           | 36         | 30         | II  | 922    | 4.4 | 8.5 | 11.1 | 36 | 21.0 | 2.13 |
| T32-25-30-36S | 2500              | 22 - 64           | 30         | 36         | II  | 922    | 4.4 | 8.1 | 11.6 | 36 | 21.0 | 2.13 |
| T32-25-36-36S | 2500              | 22 - 64           | 36         | 36         | II  | 948    | 4.4 | 8.9 | 11.7 | 36 | 21.0 | 2.13 |
| T32-35-30-18S | 3500              | 21 - 63           | 30         | 18         | II  | 924    | 4.8 | 6.6 | 11.1 | 36 | 23.0 | 2.00 |
| T32-35-36-18S | 3500              | 21 - 63           | 36         | 18         | II  | 937    | 4.8 | 7.0 | 11.1 | 36 | 22.6 | 2.00 |
| T32-35-42-18S | 3500              | 21 - 63           | 42         | 18         | II  | 950    | 4.8 | 7.4 | 11.1 | 36 | 22.6 | 2.00 |
| T32-35-30-24S | 3500              | 21 - 63           | 30         | 24         | II  | 945    | 4.8 | 6.8 | 11.4 | 36 | 22.6 | 2.00 |
| T32-35-36-24S | 3500              | 21 - 63           | 36         | 24         | II  | 963    | 4.8 | 7.3 | 11.4 | 36 | 23.0 | 2.00 |
| T32-35-42-24S | 3500              | 21 - 63           | 42         | 24         | II  | 980    | 4.8 | 7.8 | 11.4 | 36 | 23.0 | 2.00 |
| T32-35-30-30S | 3500              | 21 - 63           | 30         | 30         | II  | 967    | 4.8 | 7.0 | 11.7 | 36 | 22.6 | 2.00 |
| T32-35-36-30S | 3500              | 21 - 63           | 36         | 30         | II  | 989    | 4.8 | 7.5 | 11.8 | 36 | 22.6 | 2.00 |
| T32-35-42-30S | 3500              | 21 - 63           | 42         | 30         | II  | 1010   | 4.8 | 8.2 | 11.9 | 36 | 23.0 | 2.00 |
| T32-35-30-36S | 3500              | 21 - 63           | 30         | 36         | II  | 989    | 4.8 | 7.2 | 12.2 | 36 | 22.6 | 2.00 |
| T32-35-36-36S | 3500              | 21 - 63           | 36         | 36         | II  | 1015   | 4.8 | 7.8 | 12.3 | 36 | 22.6 | 2.00 |
| T32-35-42-36S | 3500              | 21 - 63           | 42         | 36         | II  | 1040   | 4.8 | 8.1 | 12.5 | 36 | 23.0 | 2.00 |
| T32-35-30-42S | 3500              | 21 - 63           | 30         | 42         | II  | 1010   | 4.8 | 7.3 | 12.8 | 36 | 22.6 | 2.00 |
| T32-35-36-42S | 3500              | 21 - 63           | 36         | 42         | II  | 1040   | 4.8 | 8.6 | 13.0 | 36 | 22.6 | 2.00 |
| T32-35-42-42S | 3500              | 21 - 63           | 42         | 42         | II  | 1071   | 4.8 | 8.9 | 13.2 | 36 | 23.0 | 2.00 |



| Model No.     | Capacity @ 24" LC | Range Inside Arms | Arm Length | Arm Height | Mtg    | Weight | ET  | HCG | VCG  | A  | B    | C    |
|---------------|-------------------|-------------------|------------|------------|--------|--------|-----|-----|------|----|------|------|
| T32-50-30-18S | 5000              | 23 - 74           | 30         | 18         | II/III | 1197   | 5.5 | 5.1 | 12.3 | 43 | 25.0 | 2.00 |
| T32-50-36-18S | 5000              | 23 - 74           | 36         | 18         | II/III | 1210   | 5.5 | 5.4 | 12.3 | 43 | 25.0 | 2.00 |
| T32-50-42-18S | 5000              | 23 - 74           | 42         | 18         | II/III | 1223   | 5.5 | 5.8 | 12.2 | 43 | 25.0 | 2.00 |
| T32-50-48-18S | 5000              | 23 - 74           | 48         | 18         | II/III | 1236   | 5.5 | 6.2 | 12.2 | 43 | 25.0 | 2.00 |
| T32-50-30-24S | 5000              | 23 - 74           | 30         | 24         | II/III | 1218   | 5.5 | 5.3 | 12.5 | 43 | 25.0 | 2.00 |
| T32-50-36-24S | 5000              | 23 - 74           | 36         | 24         | II/III | 1236   | 5.5 | 5.7 | 12.5 | 43 | 25.0 | 2.00 |
| T32-50-42-24S | 5000              | 23 - 74           | 42         | 24         | II/III | 1253   | 5.5 | 6.1 | 12.5 | 43 | 25.0 | 2.00 |
| T32-50-48-24S | 5000              | 23 - 74           | 48         | 24         | II/III | 1270   | 5.5 | 6.7 | 12.4 | 43 | 25.0 | 2.00 |
| T32-50-30-30S | 5000              | 23 - 74           | 30         | 30         | II/III | 1240   | 5.5 | 5.4 | 12.7 | 43 | 25.0 | 2.00 |
| T32-50-36-30S | 5000              | 23 - 74           | 36         | 30         | II/III | 1262   | 5.5 | 5.9 | 12.8 | 43 | 25.0 | 2.00 |
| T32-50-42-30S | 5000              | 23 - 74           | 42         | 30         | II/III | 1283   | 5.5 | 6.5 | 12.8 | 43 | 25.0 | 2.00 |
| T32-50-48-30S | 5000              | 23 - 74           | 48         | 30         | II/III | 1305   | 5.5 | 7.1 | 12.8 | 43 | 25.0 | 2.00 |
| T32-50-30-36S | 5000              | 23 - 74           | 30         | 36         | II/III | 1262   | 5.5 | 5.6 | 13.1 | 43 | 25.0 | 2.00 |
| T32-50-36-36S | 5000              | 23 - 74           | 36         | 36         | II/III | 1288   | 5.5 | 6.2 | 13.2 | 43 | 25.0 | 2.00 |
| T32-50-42-36S | 5000              | 23 - 74           | 42         | 36         | II/III | 1313   | 5.5 | 6.8 | 13.3 | 43 | 25.0 | 2.00 |
| T32-50-48-36S | 5000              | 23 - 74           | 48         | 36         | II/III | 1339   | 5.5 | 7.5 | 13.4 | 43 | 25.0 | 2.00 |
| T32-50-30-42S | 5000              | 23 - 74           | 30         | 42         | II/III | 1283   | 5.5 | 5.8 | 12.8 | 43 | 25.0 | 2.00 |
| T32-50-36-42S | 5000              | 23 - 74           | 36         | 42         | II/III | 1313   | 5.5 | 6.4 | 12.9 | 43 | 25.0 | 2.00 |
| T32-50-42-42S | 5000              | 23 - 74           | 42         | 42         | II/III | 1344   | 5.5 | 7.1 | 13.0 | 43 | 25.0 | 2.00 |
| T32-50-48-42S | 5000              | 23 - 74           | 48         | 42         | II/III | 1374   | 5.5 | 7.8 | 13.0 | 43 | 25.0 | 2.00 |

Things we need to know...

- ✔ Weight of Load
- ✔ Load
- ✔ Type of Product
- ✔ Length of Load
- ✔ Max. Width of
- ✔ Min. Width of Load
- ✔ Height of Load
- ✔ Forklift Capacity