


T9A Series Appliance Clamp



Hydraulic Requirements: Double function auxiliary kit

Model No.	Capacity @ 24" LC	Range Inside Pads	Pad Reach	Pad Height	Mtg	Weight	Clearance			Frame Width	
							ET	HCG	VCG	Frame Width	B
T9-25-15-36A	2500	22 - 73	15	36	II	944	6.1	5.7	13.1	44	21.3
T9-25-15-40A	2500	22 - 73	15	40	II	970	6.1	5.9	13.8	44	21.3
T9-25-15-45A	2500	22 - 73	15	45	II	1003	6.1	6.2	14.8	44	21.3
T9-25-15-54A	2500	22 - 73	15	54	II	1062	6.1	6.7	16.7	44	21.3
T9-25-15-60A	2500	22 - 73	15	60	II	1103	6.1	6.9	18.1	44	21.3
T9-25-15-72A	2500	22 - 73	15	72	II	1181	6.1	7.4	21.3	44	21.3

Arms open and close equally and sideshift left or right

Maximum Pressure

2250 psi (150 bar)

Recommended Flow

6 gpm (27 litres)

Optional Auxiliary Hydraulics

3 way pressure reducing valve

Variable pressure reducing valve

Pressure gauge

Quick disconnect couplings

Things we need to know...



Weight of Load



Max. Width of Load



Min. Width of Load



Height of Load



Length of Load



Type of Product



Forklift Capacity